

G10SH4



形名	トイシ寸法mm (標準付属品) 外径×長さ×穴径	電源 V	電流 A	消費電力 W	回転数 min ⁻¹ /回/分	質量 kg	コード m	標準付属品	トイシ取付け シャフト寸法mm 径(ねじピッチ)×長さ
G 10SH4	100×3.5×15	100	7.4	720	12,000	1.6	3心・2.5	レジノイドフレキシブルトイシ(#36) スパナ ホイルワッシャ(ダイヤ用)(コードNo.310695) (PDH-100H/(E)のみ付属)	10(1.5)×10
G 10SH4(E)		●200	3.7						
G 10SL4		100	7.4						
G 10SL4(E)		100	7.4	720	9,000	1.6	3心・2.5		
G 10SP4		100	7.4	720	12,000	1.5	2心・2.5		
G 10SM3		100	7.4	720	9,000	1.5	2心・2.5		
G 10SH3	100×3.5×15	100	7.4	720	12,000	1.6	3心・2.5		
G 10SH3(E)		●200	3.7						
G 10SL3		100	7.4						
G 10SL3(E)		100	7.4	720	9,000	1.6	3心・2.5		
G 10SP3		100	7.4	720	12,000	1.5	2心・2.5		
G 10SM2		100	7.4	720	9,000	1.5	2心・2.5		
G 10MH	100×5×15	100	7.4	720	12,000	1.6	2心・2.5	レジノイドトイシ(A36Q)、スパナ	
G 10ML		100	7.4	720	9,000	1.6	2心・2.5		
PDA-100H	100×5×15	100	8.0	760	12,000	1.9	3心・2.5	レジノイドトイシ(A36Q)、スパナ	
PDA-100H(E)		●200	4.0						
PDH-100H		100	8.0	760	9,500	1.9	3心・2.5		
PDH-100H(E)	100×4×15	100	5.5	530	12,000	1.8	3心・2.5	レジノイドトイシ(A36Q)、スパナ	
G 10SB1/(E)		100	7.0	670	12,000	1.5	2心・2.5	レジノイドフレキシブルトイシ(#36)、六角棒スパナ	

G18SP



形名	トイシ寸法mm (標準付属品) 外径×長さ×穴径	電源 V	電流 A	消費電力 W	回転数 min ⁻¹ /回/分	質量 kg	コード m	標準付属品	トイシ取付けシャフト寸法mm 径(ねじピッチ)×長さ
G 13SM3	125×3.7×22	100	7.4	720	9,000	1.7	2心・2.5	レジノイドフレキシブルトイシ(#36) スパナ、サイドハンドル	16(2.0)×14
G 13SH4		100	7.4						
G 13SH4(E)		●200	3.7						
G 13SM2	125×3.7×22	100	7.4	720	9,000	1.7	2心・2.5		
G 13SH3		100	7.4						
G 13SH3(E)		●200	3.7						
G 13S4	125×5×22	100	8.0	760	9,500	2.0	3心・2.5		
G 13S4(E)		●200	4.0						
G 13SP	125×3.7×22	100	9.0	860	9,500	2.4	2心・2.5		
G 15SP	150×4×22	●200	4.5						
G 18SP	180×3.7×22	100	11.0	1,050	8,000	3.2	2心・2.5		
		●200	5.5						
PDH-180C	180×6×22	100	12.0	1,140	6,800	3.3	2心・2.5		
		●200	6.0						
		100	14.0	1,330	6,800	6.3	3心・2.5		
G 18SH	180×6×22	100	7.0	1,430	6,800	4.9	2心・2.5	レジノイドトイシ(A36Q) スパナ、六角棒スパナ サイドハンドル	
		●200	7.5						
PDH-205A	205×6×22	100	14.0	1,330	6,000	6.5	3心・2.5		
		●200	7.0						

●印の単相200V品→在庫機種(即納)又は注文生産機種(納期約3か月)